

COMMERCIAL DOCUMENTATION



3D - LIFTING SYSTEMS | SBKM STEEL RECESS FORMER WITH MAGNET





ATTACHMENT OF THE SLOT - ANCHORS IN CONCRETE

There must be a cavity in the concrete in order to link the TH2 lifting clutch to the T-slot anchor. This cavity is spherical in shape and can be either a half ball or a small ball slot. Various support kits are available for making this recess. For a half ball cavity, the TH2 lifting clutch can be attached in any direction and can ultimately turn in the cavity during lifting until the lifting hook has reached its proper position. The RB recess former is the most practical.

RECESS FORMERS

The anchors are fitted in the mould with a recess former. The cavity former, enables the lifting clutch to fit over the anchor. Because of the special design, there are no sharp edges on the precast element. The recess formers are of course available in the same range as the lifting clutches and the anchors. This is indicated by a load group, marked on the top.


The formers are mounted on the mould with fixing plates. After demoulding the element, the recess formers can be removed easily. Another option is represented by the magnetic and steel recess formers.

The standard recess formers are made of rubber shore 65° - 70°. The rubber used has a good resistance to demould oil. The formers will keep their original shape, even when they are heated up to 120°C. They can be used many times. The steel magnetic recess formers are manufactured without rubber.

SBKM - STEEL RECESS FORMER WITH MAGNET


The SBKM steel recess former with magnets is made of S355 galvanised and is used in combination with T-slot anchor, O anchor, TPA anchor, TKS, TSG anchor and TKSG anchor. When these anchors are used, a rubber ring RR should be fitted as well. These recess formers are mostly applied in an upside down position.

Round steel recess former SBK		Load group	ØA	В	øс	ØD	h	R
Description	Product no.	[kN]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]
SBKM-013	64611	13	M12	11	20	63	36	32
SBKM-025	64612	25	M12	11	30	80	43.5	69
SBKM-050	64613	50	M12	13	37	100	54	65
SBKM-100	64614	100	M16	15	48	129	72	80





CONTACT



TERWA is the global supplier for precast and construction solutions with multiple offices around the world. With all our staff, partners and agents we are happy to give all construction and precast companies who work in the building industry a full service and 100% support.

TERWA CONSTRUCTION GROUP

Terwa Construction Netherlands (HQ)

Global Sales & Distribution Kamerlingh Onneslaan 1-3 3401 MZ IJsselstein The Netherlands

T+31-(0)30 699 13 29

F +31-(0)30 220 10 77

E info@terwa.com

Terwa Construction Poland

Sales & Distribution UI. Cicha 5 lok. 4

00-353 Warszawa

Poland

E info@terwa.com

Terwa Construction Central East Europe

Sales & Distribution

Strada Sânzienei 507075 Ghimbav Romania

T+40 372 611 576

E info@terwa.com

Terwa Construction India & Middle East Sales & Distribution

India

T+91 89 687 000 41

E info@terwa.com

Terwa Construction China Sales & distribution

5F 504, No. 101 Chuanchang road PRC, 200032, Shanghai China

E info@terwa.com

ALL SPECIFICATIONS CAN BE CHANGED WITHOUT PREVIOUS NOTICE.

DISCLAIMER

Terwa B.V. is not liable for deviations due to wear of the products it has delivered. Neither is Terwa B.V. liable for damage due to inaccurate and/or improper handling and use of the products it has delivered and/or use of same for purposes other than those intended.

Terwa B.V.'s responsibility is furthermore limited in accordance with article 13 of the "Metaalunie" conditions, which are applicable for all Terwa B.V. deliveries. The user is responsible for ensuring compliance with all applicable copyright laws. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), or for any purpose, without the express written permission of Terwa B.V.